

SAFETY-VAC[®]

PATENTED



SAFETY-VAC[®] Model 14E55-4HC

Power System

- FPZ 1.5 hp regenerative vacuum blower rated for Class I Hazmat service
- Vacuum 5HG, 75 CFM
- 115 Volt single phase power requirement
- 1.5" diameter suction and pressure ports
- Reverse-flow evacuation and transfer cycle allows operator to use the pressure port to rapidly offload recovered material

Recovery & Containment

- 55 gallon recovery drum grounded to power system
- Automatic overfill protection
- 25 feet of 1.5" fuel rated hose with end-to-end electrical continuity
- 18" surface recovery tool and wand extension with replaceable neoprene squeegee blades and height adjustment for multi-surface operation

Platform

- 46" x 30" steel frame cart with four wheels
- Stainless steel fasteners
- Static grounding reel with 25' cable
- Aluminum "quick connect" fittings on drums and hoses
- 1 year warranty from manufacturer

Service Rating

- High speed surface recovery of low viscosity materials from distances up to 30 ft

Options

- Baldor 1.0 HP AC vacuum motor, switches and power cord connections UL rated for CLASS I & II hazardous location service
- Replaceable cartridge-type particle filter
- Stainless steel deck

Advance Compliance Systems LLC.

866.477.4569 / 352.373.7055 / Fx 352.378.2699