

SAFETY-VAC[®]

PATENTED



SAFETY-VAC[®] Model 15G55-3TC

Power System

- Subaru Robin Model EX17 6 hp air-cooled engine
- No-spill oil drain for ease of maintenance
- Full spark arrest
- FPZ K5 or Siemens 15 High pressure regenerative blower system
- Vacuum 8.5 in. HG, up to 200 CFM (see Service Rating for capabilities)

Recovery & Containment

- One 55 gallon drum vacuum recovery system with detachable drum bracket
- Automatic overfill protection
- 2" diameter suction and pressure ports
- 25 feet of 1.5" fuel rated recovery hose with end-to-end electrical continuity
- 20" surface recovery tool and wand extension with replaceable neoprene squeegee blades and height adjustment for multi-surface operation
- Aluminum quick-connect hose fittings
- Reverse flow evacuation and transfer cycle allows operator to use pressure side blower power to rapidly offload recovered liquids (pump-out capabilities)

Platform

- Three wheel custom cart for manual operator mobility and towing
- Stainless steel fasteners
- Ball bearing wheel hubs with pneumatic tires
- Complete machine weight including full fuel tank: 414 lbs.
- Dimensions: Width – 51 inches Length – 39 inches

Service Rating

- High speed recovery of low to medium viscosity material from distances up to 25' from unit at depths to eight feet below grade (50' recovery distance at grade level)
- Aircraft type ignition grounding and frame grounding cable
- One year warranty from manufacturer

Options

- Diesel engine
- LP Conversion

Advance Compliance Systems LLC.

866.477.4569 / 352.373.7055 / Fx 352.378.2699