

SAFETY-VAC®

PATENTED



SAFETY-VAC® Model 35LRP200-DOT-T

Power System

- 10 hp air-cooled electric start Yanmar diesel engine
- No spill oil drain
- Full spark arrest
- Dual V-belt drive
- Liquid ring pump system
- Vacuum 24 HG @ 200 CFM

Recovery & Containment

- One 200-gallon tank with access hatch
- Automatic system overflow protection
- 2" diameter suction and pressure ports
- 50' capacity live vacuum hose reel
- 50' of 2" fuel rated hose
- Recovery hose is neoprene with end-to-end electrical continuity
- 18" surface recovery tool and wand extension with replaceable neoprene squeegee blades and height adjustment for multi-surface operation
- "Stinger" recovery tool for tank and sump recovery
- Aluminum quick-connect hose fittings
- Reverse flow evacuation and transfer cycle allows operator to use pressure-side blower power to rapidly offload recovered material
- 50' static grounding reel
- Tank drain valve

Platform

- 5' x 8' 3500 lb gross vehicle weight trailer
- Stainless steel fasteners
- Wheel hubs have electric brakes

Service Rating

- High speed liquid and particle recovery from ground level to 25' below grade
- Powered emptying and liquid transfer
- One year warranty from engine and blower manufacturers
- Two year warranty on material workmanship and containment

Advance Compliance Systems LLC.

866.477.4569 / 352.373.7055 / Fx 352.378.2699